

	11-20.1							
2/3" 1.4/12		1/2"	1/3"					
FOCAL LENGTH	f=12mm							
MAX. DIAMETER (RATIO)	F=1:1.4~16							
ELEMENT	6 Elements in 6 Groups							
PICTURE SIZE	6.6x8.8mm	4.8x6.4	3.6×4.8					
ANGLE VER. ANGLE	31.7°	23.0 *	17.2 °					
HOR. ANGLE	42.5°	30.7 °	23.0 °					
DIA. ANGLE	53.7°	38.5 *	28.8 *					
DISTORTION (TV)	-2.5%	-1.2%	-0.6%					
SHOOTIG RANGE AT <u>VER.</u>	117mm	84mm	62mm					
MINIMUM FOCUSHOR.	161mm	113mm	84mm					
DISTANCE DIA.	209mm	145mm	106mm					
MINIMUM FOCUS DISTANCE	NIMUM FOCUS DISTANCE O.1m O.2m 光学保証範囲							
FLANGE BACK	17.526 mm in air							
BACK FOCUS	11.12mm in air							
FILTER SCREW SIZE	M27×0.5							
FRONT/REAR EFFECTIVE DIA.	Front: Ø 12.3mm	Rear: Ø	11.7mm					
MOUNT	C-MOUNT							
EXIT PUPIL	-38.9mm							
TEMPERATURE RANGE	-10~+45°C							
STORNG TEMPERATURE RANGE	-40~+60°C							
RESOLUTION CENTER/CORNER	Center100line/mm	Corner	60line/mm					
WEIGHT	63g							

注)本仕様書については、予告なしに変更する場合があります。



		尺度	1/1	承認	製図
		機種名	LM12JC		
04.12.21	作成年月日	機種番	2/3" 1.4/12mm		