

2/3" 1.6	5/2	5mm C	_	1/2"	1/3"		
FOCAL LENGTH		f=25mm					
MAX. DIAMETER (RATIO)		F=1:1.6~16					
ELEMENT		5 Elements in 5 Groups					
PICTURE SIZE		6.6x8.8mm		8x6.4	3.6×4.8		
ANGLE VER. AND	GLE	15.7°		1.4	8.6 *		
HOR. AND	<u> JLE</u>	21.0°		5.3 *	11.5		
DIA. ANGLE		26.3°	19	9.1	14.3 °		
DISTORTION (TV)		-0.6%	-	0.2%	-0.1%		
SHOOTIG RANGE AT		89mm	9	4mm	48mm		
MINIMUM FOCUS	HOR.	119mm	8	6mm	64mm		
DISTANCE	DIA.	150mm	1(08mm	80mm		
MINIMUM FOCUS DISTANCE		0.2m 0.3m 性能保証範囲					
FLANGE BACK		17.526 ₩ mm in air					
BACK FOCUS		10.32mm	in a	<u>ir </u>			
FILTER SCREW SIZE		M27×0.5					
FRONT/REAR EFFECTIVE DIA.		Front: Ø 14.6mm		Rear: Ø 10.7mm			
MOUNT		C-MOUN	Τ				
EXIT PUPIL		-26.2mm					
TEMPERATURE RANGE		-10~+50					
STORNG TEMPERATURE		-20~+60					
RESOLUTION CENTER/	CORNER	Center100li <u>n</u> e		Corner	60line/mm		
WEIGHT		58	3g				



		尺度	1/1	承認		製 図
		機種名	LM25JC			
10.01.06	作図修正	機	2	/~"	1.6/2	'5mm
04.12.21	作成年月日	種番	2/	ر	1.07 Z	ווווווכ