

2/3" 1.6/3	1/2"	1/3"				
FOCAL LENGTH						
MAX. DIAMETER (RATIO)	F=1:1.6~16					
ELEMENT	6 Elements in 4 Groups					
PICTURE SIZE	6.6x8.8mm	4.8×6.4	4.8×3.6			
ANGLE VER. ANGLE	10.8°	7.9°	5.9°			
HOR. ANGLE	14.4°	10.5°	7.9°			
DIA. ANGLE	17.9°	13.1°	9.8°			
DISTORTION (TV)	-0.21%	-0.12%	-0.08%			
SHOOTIG RANGE AT VER.	94.7 mm	68.8	51.6			
MINIMUM FOCUSHOR.	126.6mm	91.9	68.8			
DISTANCE DIA.	158.7 mm	115.0	86.1			
MINIMUM FOCUS DISTANCE	0.3m 0.5m 性能保証範囲					
FLANGE BACK	17.526 mm i	n air				
BACK FOCUS	14.9mm in air					
FILTER SCREW SIZE	M30.5x0.5					
FRONT/REAR EFFECTIVE DIA.	Front: Ø 21.7mm	Rear: Ø 12.9	:.9mm			
MOUNT	C-MOUNT					
EXIT PUPIL	-40.6mm					
TEMPERATURE RANGE	-10~+45° C					
STORNG TEMPERATURE RANGE	-20~+60°C					
RESOLUTION CENTER/CORNER	Center100line/mm	Corner	60line/mm			
WEIGHT	85g					

注)本仕様書については、予告なしに変更する場合があります。



		尺度	1/1	承認	杉田	製図	杉田
		機種名	LM35JC				
04.12.22	作成年月日	機種番	2/3"	F	1.6 f=	:35	mm