



2/3" 1.4/ 8mm C		1/2"	1/3"
FOCAL LENGTH		f=8mm	
MAX. DIAMETER (RATIO)		F=1:1.4~16	
ELEMENT		7 Elements in 6 Groups	
PICTURE SIZE		6.6x8.8mm	4.8x6.4 3.6x4.8
ANGLE	VER. ANGLE	47.7°	34.6° 28.6°
	HOR. ANGLE	64.2°	46.2° 34.5°
	DIA. ANGLE	81.3°	58.1° 43.3°
DISTORTION (TV)		-6.2%	-2.5% -1.3%
SHOOTING RANGE AT	VER.	184mm	129.3mm 95.5mm
MINIMUM FOCUS	HOR.	260mm	177.5mm 129.3mm
DISTANCE	DIA.	356mm	231.0mm 165.1mm
MINIMUM FOCUS DISTANCE		0.1m	0.2m 光学保証範囲
FLANGE BACK		17.526	mm in air
BACK FOCUS		11.30mm	in air
FILTER SCREW SIZE		M27x0.5	
FRONT/REAR EFFECTIVE DIA.		Front: Ø 17.4mm	Rear: Ø 11.1mm
MOUNT		C-MOUNT	
EXIT PUPIL		-27.0mm	
TEMPERATURE RANGE		-10~+45° C	
STORNG TEMPERATURE RANGE		-40~+60° C	
RESOLUTION CENTER/CORNER		Center 100line/mm	Corner 60line/mm
WEIGHT		60g	

注) 本仕様書については、予告なしに変更する場合があります。



		尺度	1/1	承認	製
		機種名	LM8JC		
		機種番	2/3" 1.4/8mm		
04.12.21	作成年月日				