

SAPPHIRE series

S-49A70 CXP

Adimec
Excellence in Imaging



The SAPPHIRE 49 Megapixel camera delivers a superior performance in a 7008x7000 pixels resolution running at 70 fps. It uses state of the art global shutter sensor technology. The S-49A70 offers a high dynamic range with low noise levels and a high sensitivity. The camera is compatible with other CoaXPress cameras in the SAPPHIRE series: S-25, S-50 and S-49A35.

The S-49A70 CoaXPress camera comes in a low power, compact outline design without forced cooling through a fan. This provides optimal design freedom for system integration with maximum system reliability. The camera offers Adimec Connect & Grab™ allowing engineers to start system development.


Typical applications examples:

Semiconductors metrology tools; Display Inspection; Solar panel inspection; Medical

CoaXPress®



7008 x 7000 at 70 fps



Active sensor alignment



Low noise performance



Device-to-device repeatability



Low frequency flat field correction in bright



Configurable quad CXP12 speed

High Resolution Metrology Camera

49 Megapixel

Target Specifications


S-49A70 CXP	
Sensor	Gpixel GMAX3249
Pixel size	3.2 μm x 3.2 μm with micro lenses
Resolution	7008 (H) x 7000 (V)
Optical format	37,4 mm (29.9 x 22.4 mm)
Video Output	CoaXPress - CXP3/6/10/12 - 1, 2, 4 lanes configurable
Max frame rate	70 fps
Dynamic range	62.3 dB
Full Well	10.9 ke ⁻
Electronic shutter	CMOS progressive scan Global Shutter (PLS <1/15000)
Image acquisition	Timed, TriggerWidth, SyncControl, TimedTriggerControl
Output resolution	8 / 10 / 12 Bit
Monochrome / Color	Monochrome / Color
Power input	24 Vdc PoCXP
Power usage	< 15 W @ 24Vdc
Sensor temperature	+5°C to +70°C
Reliability	MTBF > 75,000 h @ 30°C
Weight	400g +/- 5% excluding lens mount
Lens mount (optional)	F, M42, T2, TFL-II mount
Compliance	CE, ROHS

Functionality

		
Defect pixel correction	√	√
Manual and one push white balance	-	√
Programmable look-up table	√	√
Digital fine gain (1x to 32x)	√	√
Mirroring	√	√
Band ROI	√	√
Binning	√	√
Pixel based DSNU correction	√	√
Column based PRNU correction	√	√
Low Frequency Flat Field Correction (LF FFC)	√	√
Sensitivity matching between cameras	√	√
Programmable I/O	√	√
User data storage	*	*

√: standard -: Not available *: Available on request

Dimensions



Adimec support

Adimec SAPPHERE cameras are designed, optimized and calibrated for demanding inspection and metrology applications.

Additionally the Adimec application experts support our customers in integrating the SAPPHERE camera and tuning the images to fit their measurement.

Please contact your Adimec representative for further assistance.

For maximum image quality, performance, and reliability in demanding applications - Choose Adimec

North America	Europe	Japan & Korea	Asia - Pacific	China
Phone: (+1) 781-279-0770	(+31) 40-2353900	(+81) 3-5968-8377	(+65) 6334-1236	(+86)21 6266 1692
Fax: (+1) 781-279-0771		(+81) 3-5968-8388	(+65) 6334-1436	
E-mail salesus@adimec.com	saleseu@adimec.com	salesjp@adimec.com	salesap@adimec.com	salescn@adimec.com.cn