

## CoaXPress – CXP6

### Product Information

Designed for CoaXPress this cable assembly provides a robust interconnect. The PVC jacket and solid core provide a rugged interconnect solution for a wide variety of stationary applications. The cable assemblies are available with your choice of BNC, HD-BNC or DIN 1.0/2.3 connectors as well as fully customizable lengths.

### Main Features

- Precision 75-ohm impedance
- PVC Jacket
- 20 awg solid center conductor
- Designed for static applications



### Specification

Cable Specifications	
Overall Diameter	.232 / 5.9 mm
Maximum Length	CXP 3 ~ 70 meters CXP 6 ~ 28 meters
Maximum Operating Temperature	80°C
Jacket Color	Black
Minimum Bend Radius	7 x OD

### Ordering Information

Order Number	Description
S-CXP-xx-P	CoaXPress BNC to BNC
S-CXP-xx-DIN	CoaXPress BNC to DIN 1.0/2.3
S-DIN-xx-DIN	CoaXPress DIN 1.0/2.3 to DIN 1.0/2.3
S-HCXP-xx-DIN	CoaXPress HD BNC to DIN 1.0/2.3
S-HCXP-xx-P	CoaXPress HD BNC to BNC
S-HCXP-xx-HP	CoaXPress HD BNC to HD BNC

Replace XX with length in meters. Custom variations available, please contact customer service for additional information.