



2/3" 1.4/25mm C		1/2"	1/3"
FOCAL LENGTH		f=25mm	
MAX. DIAMETER (RATIO)		F=1:1.4,4,8,16	
ELEMENT		6群 8枚	
PICTURE SIZE		6.6x8.8mm	4.8x6.4
ANGLE	VER. ANGLE	14.8°	10.5°
	HOR. ANGLE	19.6°	14.0°
	DIA. ANGLE	24.3°	17.5°
DISTORTION (TV)		-0.04%	-
SHOOTING RANGE AT	VER.	53.3 mm	38.7
MINIMUM FOCUS	HOR.	71.1 mm	51.7
DISTANCE	DIA.	89.0 mm	64.6
MINIMUM FOCUS DISTANCE		0.2m	
FLANGE BACK		17.526 mm in air	
BACK FOCUS		11.7mm in air (Mechanical 10.2mm in air)	
FILTER SCREW SIZE		M27x0.5	
FRONT/REAR EFFECTIVE DIA.		前φ24.0mm	後φ12.8mm
MOUNT		C-MOUNT	
EXIT PUPIL		-80.0	
TEMPERATURE RANGE		-10~+50°C	
STORAGE TEMPERATURE RANGE		-20~+60°C	
RESOLUTION CENTER/CORNER		中心100本/mm	周辺 80本/mm
WEIGHT		g	

NOTE: Specifications and availability are subject to change without notice
 注) 本仕様については、予告なしに変更する場合があります。



		尺度	1/1	承認	八木	製図	八木
		機種名	2/3" F1.4 f=25mm				
2014.2.25	作成年月日	LM25JCM-V					